

APDatec 920 blaugedeckt

Single layer Polyethylene tube

- Applications** pneumatics, vehicle construction, compressors, automation technology & robotics, compressed air
- Structure** PE, blue, opaque
- Temperature** -30°C up to 70°C
- Properties** good temperature resistance, , smooth inside, smooth outside



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
2	4,00	1,00	24	15,00	45,00	0,00900	0,90	100	9200041000
2	4,00	1,00	20	15,00	45,00	0,00900	0,45	50	92080041050
4	6,00	1,00	36	8,00	32,00	0,01500	0,75	50	9200061050
5	8,00	1,50	60	8,00	24,00	0,02900	2,90	100	92080081500
6	8,00	1,00	48	8,00	24,00	0,02000	2,00	100	9200081000
6	8,00	1,00	48	8,00	24,00	0,02000	1,00	50	9200081050
6	10,00	2,00	40	12,00		0,02900	2,90	100	9200102000
7	10,00	1,50	60	8,00	24,00	0,03700	3,70	100	9200101500
8	10,00	1,00	60	8,00	24,00	0,03700	3,70	100	9200101000
9	12,00	1,50	72	6,00	18,00	0,48000	24,00	50	92080121550