

APDatec 910 blaugedeckt

Single layer Polyamide tube of PA 11/12

- Applications** pneumatics, automation technology & robotics, welding technology, vehicle construction, compressors
- Structure** PA, blue, opaque
- Temperature** -40°C up to 90°C
- Properties** good temperature resistance, high pressure resistance, smooth inside, smooth outside



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
2	4,00	1,00	20	40,00	0,01000	1,00	100	9100041000
2	4,00	1,00	20	40,00	0,01000	0,50	50	910B0041050
3	5,00	1,00	25	35,00	0,01350	1,35	100	9100051000
4	6,00	1,00	30	25,00	0,01600	1,60	100	9100061000
4	6,00	1,00	30	25,00	0,01600	0,80	50	910B0061050
6	8,00	1,00	40	20,00	0,02260	2,26	100	9100081000
6	8,00	1,00	40	20,00	0,02260	1,13	50	910B0081050
8	10,00	1,00	60	15,00	0,03000	3,00	100	9100101000
9	12,00	1,50	75	17,00	0,05300	2,65	50	910B0121550
10	12,00	1,00	60	13,00	0,03600	1,80	50	9100121050
11	14,00	1,50	85	14,00	0,06200	6,20	100	9100141500
27	4,00	0,65	20	30,00	0,01000	0,50	50	910B0040650