

## APDatec 925 blaugedeckt

Single layer Polyamide tube of PA 11/12

<b>Applications</b>	automation technology & robotics, pneumatics, vehicle construction, compressors, compressed air
<b>Structure</b>	TPU / Polyether-Polyurethane, blue, opaque
<b>Temperature</b>	-35°C up to 80°C
<b>Properties</b>	light weight, very good flexibility, good temperature resistance, very high pressure resistance, good ozone- & UV-resistance



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
2	4,00	1,00	10	9,00	0,01200	1,20	100	9250041000
2	4,00	1,00	10	9,00	0,01100	0,55	50	9250041050
4	6,00	1,00	18	9,00	0,01900	0,95	50	9250061050
6	8,00	1,00	22	9,00	0,02900	1,45	50	9250081050
7	10,00	1,50	25	9,00	0,02600	2,60	100	9250101500
8	10,00	1,00	25	9,00	0,02600	1,30	50	9250101050
8	12,00	2,00	40	9,00	0,07600	3,80	50	9250122050