


APDatec 102

Flexible PVC hose with shock-resistant rigid PVC spiral

Applications	pond technology, pump technology, irrigation, agriculture, water drain
Structure	soft PVC, black, opaque, plastic spiral / rigid PVC
Temperature	-5°C up to 60°C
Properties	good flexibility, smooth inside, corrugated outside, , weather proof, phthalate-free



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
19	23,80	2,40	80	5,00	0,69	0,20000	5,00	25	1020190250
19	23,80	2,40	80	5,00	0,69	0,20000	10,00	50	1020190500
25	30,00	2,50	110	5,00	0,69	0,25000	6,25	25	1020250250
25	30,00	2,50	110	5,00	0,69	0,25000	12,50	50	1020250500
32	37,60	2,80	135	5,00	0,69	0,32000	0,32	25	1020320250
32	37,60	2,80	135	5,00	0,69	0,32000	16,00	50	1020320500
38	44,40	3,20	160	5,00	0,69	0,42000	0,42	25	1020380250
38	44,40	3,20	160	5,00	0,69	0,42000	21,00	50	1020380500
40	46,60	3,30	170	5,00	0,69	0,47000	11,75	25	1020400250
40	46,60	3,30	170	5,00	0,69	0,47000	23,50	50	1020400500
50	56,80	3,40	220	5,00	0,69	0,64000	16,00	25	1020500250
50	56,80	3,40	220	5,00	0,69	0,64000	32,00	50	1020500500