

## APDatec 46

Flexible spiral hose made of EVA. reinforced with shock resistant hard PP spiral, phthalate-free

|                     |                                                                                                                                                            |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Applications</b> | pool & whirlpool, swimming pool technology, filter systems, water drain                                                                                    |
| <b>Structure</b>    | EVA, uncolored, transparent, plastic spiral / PP                                                                                                           |
| <b>Temperature</b>  | -20°C up to 60°C                                                                                                                                           |
| <b>Properties</b>   | good flexibility, crush-resistant, good tensile strength, smooth inside, corrugated outside, phthalate-free, hydrolysis & microbe resistant, weather proof |



| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Vacuum Max. (bar) | Weight (kg/m) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|---------------------|-------------------|---------------|-----------------------------|------------|----------------|
| 32                  | 40,00               | 0,60                | 120                 | 0,59              | 0,23000       | 11,50                       | 50         | 460320500      |
| 38                  | 47,00               | 0,80                | 130                 | 0,59              | 0,28000       | 14,00                       | 50         | 460380500      |
| 50                  | 60,00               | 0,90                | 150                 | 0,59              | 0,43000       | 21,50                       | 50         | 460500500      |