

AQUALIFE® 818 4.0 TPE

TPE drinking water hose, multi-layered

Applications	drinking water, beverage production & conveying
Structure	TPE/E, blue, opaque, cross braid
Temperature	-30°C up to 70°C, short term up to 90°C
Properties	hydrolysis & microbe resistant, weather proof, high pressure resistance, crush-resistant, smooth inside, smooth outside
Norms	DVGW W 270



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
10	15,40	2,50	70	14,00	42,00	0,09000	2,25	25	818010252504
10	15,40	2,50	70	14,00	42,00	0,09000	4,50	50	818010255004
13	18,80	3,00	70	15,00	45,00	0,14100	7,05	50	818013305004
13	18,80	3,00	70	15,00	45,00	0,14120	3,53	25	818013302504
19	26,60	4,10	130	15,00	45,00	0,23200	5,80	25	818019382504
19	27,20	4,10	130	15,00	45,00	0,23200	11,60	50	818019385004
25	34,60	4,80	220	10,00	30,00	0,40720	10,18	25	818025482504
25	34,60	4,80	220	10,00	30,00	0,40700	20,35	50	818025485004