

APDatec 811

Multilayer PVC hose with high tear resistant Polyester fabric, oil resistant

Applications	compressed air, fuel delivery, construction machines, vehicle construction, compressors
Structure	PVC, uncolored, transparent, cross braid
Temperature	-20°C up to 65°C
Properties	good flexibility, high pressure resistance, good oil & petrol resistance, good resistance to compressed air containing mineral oil, very good chemical resistance, weather proof



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
6	12,00	3,00	25	25,00	75,00	0,10400	5,20	50	8110063050
9	15,00	3,00	35	22,00	66,00	0,14400	7,20	50	8110093050
12	21,00	4,50	55	20,00	60,00	0,29700	14,85	50	8110124550
13	19,00	3,00	70	15,00	45,00	0,19200	9,60	50	8110133050
19	27,00	4,00	130	11,00	33,00	0,36800	18,40	50	8110194050
25	34,00	4,50	220	8,00	24,00	0,53120	13,28	25	8110254525
32	42,00	5,00	310	8,00	24,00	0,74000	18,50	25	8110325025